

CAPACITANCE TYPE LEVEL TRANSMITTER



ELTRAN

ELTRAN 701 ABS : CONDUCTING LIQUID
ELTRAN 702 ABS : NONCONDUCTING LIQUID
ELTRAN 703 ALUMINIUM : CONDUCTING LIQUID
ELTRAN 704 ALUMINIUM : NONCONDUCTING LIQUID




TECHNICAL SPECIFICATION

MEASURING RANGE	: 50 TO 2000 mm RUGGEDPROBE 2000 TO 10000 mm FLEXPBROBE
TRANSMITTER TYPE	: LOOP POWERED
SUPPLY VOLTAGE	: 12 TO 30 V DC
OUT PUT	: 4-20mA CONSTANT CURRENT
MAXIMUM LOAD RESISTANCE	: $\frac{\text{SUPPLY VOLTAGE} - 12 \text{ V}}{0.02 \text{ A}} \Omega$
PRESSURE RATING	: 6 Kg/cm ²
TEMPERATURE	: -20 TO 100°C
ENCLOSURE	: DIE CAST ALUMINIUM DULY APPROVED FLAME PROOF ABS DULY APPROVED FOR IP 65/ 67
RESOLUTION	: 0.1mm
ACCURACY	: $\pm 0.25 \%$ FSR



CE - 2424



An ISO 9001:2008
Certified Company

R-1 A, VILAS APPT, SANT TUKARAM
PATH, KOPRI, THANE(E) 400 603, INDIA
Fax: 91-22-2532 4845

SPINK CONTROLS®

Phone: 91-22-2532 8223/24

Email: info@spinkcontrolsindia.com

www.spinkcontrolsindia.com